

ATS22 –

230 ... 440 – 50/60

()			()			()			
230	400	440	Reference			x x	230	400	440
4	7,5	7,5	ATS22D17Q	17	39	130 X 169 X 265	5,5	11	15
7,5	15	15	ATS22D32Q	32	44	130 X 169 X 265	11	22	22
11	22	22	ATS22D47Q	47	48	130 X 169 X 265	18,5	45	45
15	30	30	ATS22D62Q	62	59	145 X 207 X 295	22	55	55
18,5	37	37	ATS22D75Q	75	63	145 X 207 X 295	30	55	75
22	45	45	ATS22D88Q	88	66	145 X 207 X 295	37	75	75
30	55	55	ATS22C11Q	110	73	150 X 229 X 356	45	90	90
37	75	75	ATS22C14Q	140	82	150 X 229 X 356	55	110	110
45	90	90	ATS22C17Q	170	91	150 X 229 X 356	75	132	132
55	110	110	ATS22C21Q	210	117	206 X 299 X 425	90	160	160
75	132	132	ATS22C25Q	250	129	206 X 299 X 425	110	220	220
90	160	160	ATS22C32Q	320	150	206 X 299 X 425	132	250	250
110	220	220	ATS22C41Q	410	177	206 X 299 X 425	160	315	315
132	250	250	ATS22C48Q	480	218	304 X 340 X 455	220	355	400
160	315	355	ATS22C59Q	590	251	304 X 340 X 455	250	400	500

- **3** _____ : 24 cc
- **1 PTC** _____ : 750 Ω 25°C, 2600 Ω 3100 Ω
- **2** _____ : 1 N/O 1 N/C

